



product description:

designed for distribution system with voltage 400 V and with maximum current 16 A  
 a large number of knockouts for introducing cables and pipes  
 possibility to install the support trunking TS 35  
 possibility to set the lid in a horizontal position  
 possibility to break the sidewall for easier cable handling  
 outer side of the bottom contains holes for marking drill holes  
 mounting screws are fitted with a triple thread for quick installation

material: PVC (Pb Free)

color: yellow

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 850 °C

fire class for underlying material: A1-F

weight: 230 g

meets the requirements: ČSN EN 60670-1, ČSN EN IEC 60670-1 ed. 2:21

storage: ČSN 64 0090

KO 125/1L\_NA - cover screws and screws for mounting into double wall inserted into box, each box with a cover V 125/1 sealed in shrink foil and labelled; 27 pcs of boxes stacked in carton

KO 125/1L\_ST - screws for mounting into double wall installed in the box, cover screwed to the box and box labelled; 27 pcs of boxes stacked in carton

accessories:

terminal plate S-66; S-96; SP-96  
 equipotential terminal plate EPS 2  
 screwless terminal plates TYP015, TYP016, TYP017, TYP018  
 support trunking TS35

auxiliary tools:

saw-drill VPT 40  
 universal carrier VPTU