

type number	Ø	height H (mm)	thickness of metal sheet (mm)	weight (kg/pc)
KPNL 15_XX	15	5	1,00	0,00160
KPNL 25_XX	25	5	0,80	0,00333



product description: The metal washer is used to attach electrical installation trunkings to the wall/ceiling.

The metal washers must be fixed using the K-PULSA_PO gas nail gun.

Fasten the cable trays using a nail gun exclusively through the holes located at the bottom of the tray.

Suitable for fastening trunkings made of PVC and HF material.

Thanks to its design, it can be easily mounting into the nailing port of the gas nail gun, allowing for one-handed installation.

KPNL 15_XX - suitable for:

LE 60, LE 80, LE 100, LO 50, LV 40x15, LV 24x22, EKE 60x60, EKE 100x60,
EKE 140x60, EKD 80x40, EKD 100x40, EKD 120x40, LH 60x40, LHD 40x20,
LHD 40x40, LHD 25x15, LHD 25x20, LHD 32x15

KPNL 25_XX - suitable for:

LE 80, LV 40x15, EKD 80x40, EKD 120x40, LHD 40x20, LHD 40x40

surface finish: galvanized

sales amount: á 200 pcs

storage: ČSN EN 60721-3-1



 WARNING**Risk of Injury Due to Improper Installation**

Always follow the safety instructions provided by the tool manufacturer when using the washer with a nail gun. Incorrect positioning or use of the washer may result in an insecure installation and subsequent loosening of the fastened component.

Risk of Hand Injury

When handling the washer and fastening components, ensure a proper grip and avoid direct hand contact in the fastening area.

Risk of Injury from Flying Debris

During fastening, material particles may be ejected. It is recommended to wear protective eyewear and gloves to prevent injury.

Safe Use

Under normal and foreseeable conditions of use, there are no risks to consumers, provided that proper installation and usage are carried out in accordance with the installation manual.

recycling codes:



washer for shooting