

type number	Α	for width of cable tray	thickness of metal sheet	max. load	weight
	mm	mm	mm	kg	kg/pc
NP 450_S	450	400	1,5	150	0,5
NP 550_S	550	500	1,5	150	0,62
NP 650_S	650	600	1,5	150	0,73
NP 450_ZM	450	400	1,5	150	0,5
NP 550_ZM	550	500	1,5	150	0,62
NP 650_ZM	650	600	1,5	150	0,73

product description:

The load bearing profile is intended as a support for the installation of cable ladders or trays. The load bearing profile is fixed by using two threaded rods ZT 10 + nut M 10 + washer PD 10

PD 10

The size of the load bearing profile is determined according to the width of the cable tray or cable ladder + 50 mm, for example for a cable tray that is 500 mm

ZM surface finish load bearing profile shall be used for ZM or F surface finish trays.

These items can also be ordered in a varnished version.

surface finish:

S - Pre-Galvanized steel according to ČSN EN 10346,

ČSN EN 10143, zinc-layer 15-27 μm

ZM - Pre-Galvanized steel with admixture of magnesium and aluminum according to ČSN EN 10346, ČSN EN 10143,

protective layer 18-31 µm

wide, order NP 550.


sales amount:

á 1 pc

meets the requirements: ČSN EN 61537:02

storage:

ČSN EN 60721-3-1







safety risks and recycling codes



MARNING

Risk of injury from cutting

Although the cable trays are produced with maximum effort to minimize sharper edges, it is necessary to wear protective gloves to carry, grip and work with cable elements.

Electricity injury

As individual components of cable management systems are made of electrical conductive material, it is essential not to work with a system near live electrical parts. Infringement of the safety regulations may cause serious injury of health or death.

Safe Use

Under normal and foreseeable conditions of use, there are no risks to consumers, provided that proper installation and usage are carried out in accordance with the installation manual.

recycling codes:



NP



cardboard